

Key **Features**

Full HD 1080p resolution | 3,500 Lumen Brightness
| Long Lamp Life | Powered USB Port | Reduced
Input Latency



Product **Description**

Perfect for home entertainment, the ViewSonic® PX700HD projector features 3,500 lumens, Full HD 1920x1080 native resolution, an intuitive, user-friendly design and a sleek black chassis. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment. An ultra-low input latency provides faster frame-by-frame action, while a Sports Mode feature delivers stunning detail so you can enjoy fast-action sports on the big screen. Full HD 3D compatibility lets you enjoy 3D movies and games. What's more, an energy-saving SuperEco® feature reduces power consumption and extends the lamp life by up to 15,000 hours*. Extensive connectivity options include dual HDMI inputs and USB power, making the PX700HD a versatile home entertainment solution.
*Lamp life may vary based on actual usage and other factors.



- 1. IR remote sensor
- 2. Projection lens
- 3. Elevation foot
- 4. Focus / zoom rings
- 5. USB type Mini B
- 6. USB 2.0 Type A (powered)
- 7. HDMI (x2)
- 8. AC In

- 9. VGA
- 10. RS232
- 11. Monitor Out
- 12. Control Panel
- 13. Kensington® Lock Slot





1920 x 1080 **RESOLUTION**



LUMENS



1.5 - 1.65 **THROW RATIO**



Tlf:. 30 32 18 89

E-mail: info@av-concept.dk Website: AV-Concept.dk

Display:	
Type:	DLP
Resolution Type:	Full HD 1080p
Resolution:	1920 x 1080
Brightness (ANSI Lumens):	3,500
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.5 - 25.0 ft / 0.7 - 7.6 m
Throw Ratio:	1.5 - 1.65
Keystone:	Vertical (± 40°)
Lens:	1.1x optical zoom
Light Source (watt):	203
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco- Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	12,000:1
Aspect Ratio:	16:9
Video Signal:	
Fraguancy Harizantal:	15K102KHz

Compatibility:	
Frequency Vertical:	23~120Hz
Frequency Horizontal:	15K~102KHZ

Compatibility.		
	PC Resolution (max):	1920 x 1200
	PC Resolution (min):	640 x 480
	Mac® Resolution (max):	1920 x 1200
	Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI(2), VGA In(1), Mini USB(1)

Audio:

Internal Speakers:	2W
Power:	
Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	350W
Stand-by:	<0.5W
Controls:	
	Bower koystone/arrow koys

Controls:	
Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%
Additional Hardware:	
Kensington Lock Slot:	1
Weight (imperial):	
Net (lbs):	8.1

Gross (kg):

Gross (lbs):	10.8
Weight (metric):	
Net (kg):	3.7

4.9

Dimensions (imperial) (WxHxD):

Packaging (in.):	16.4 x 8.2 x 13.2
Physical (in.):	13.1 x 5.3 x 10.3

Dimensions (metric) (WxHxD):

Packaging (mm):	417.0 x 207.0 x 336.0
Physical (mm):	332 0 x 135 0 x 261 0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PX700HD projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907929119

Accessories:

HB10B, PGD-350, PJ-SCW-1001W, PJ-WMK-006, PM-FCP, RLC-116, VC10,



Tlf:. 30 32 18 89

E-mail: info@av-concept.dk Website: AV-Concept.dk