

MOVE-12 - PA Loudspeaker



Professional PA Speaker Systems

which have been matched to the special requirements of mobile applications. The applied bass speakers and tweeter systems from BEYMA or FAITAL provide a high-quality sound for an excellent performance.

Professional PA speaker system, 300 W, 8 Ohm

- Professional full range bass-reflex system
- Cabinet made of birch plywood
- 30 cm (12", BEYMA) bass speaker
- 25 mm (1", 44 mm voice coil, BEYMA) horn tweeter, can be turned by 90°
- Neutral sound tuning
- Multi-purpose positioning and installation options
- "Catch & Carry" carrying handles
- M8 threaded inserts for suspended installation
- 2 x NEUTRIK SPEAKON terminal, in/out
- Stand sleeve, robust front grille
- Ball-proof acc. to DIN 18032, Part 3

DJ magazine 08/2013

"A good passive speaker system at a very attractive price. Remarkably, the speaker system already provides an excellent sound at low volume levels which hardly changes at high volume levels."

tastenwelt 04/2013

"This speaker system offers an effective sound tuning, from low to high volume levels. It provides a very



AV-Concept ApS
Glasmagervej 13, Fensmark
4684 Holmegaard
30 32 18 89
www.av-concept.dk

powerful reproduction of the human voice which can be well separated from the music signals. Thus, the MOVE-12 is also well-suited as a floor monitor. It features four ergonomically-friendly and perfectly positioned carrying handles. In the category workmanship and configuration, the MOVE-12 leaves an overall very professional impression.”

Technical data:

Active/passive	: passive
Transmission method	: -
Total output power	: -
Power rating (RMS)	: -
Total power rating	: 600 W
Power rating (RMS)	: 300 W
Impedance	: 8 Ohm
Frequency range	: 45-20,000 Hz
THD	: -
S/N ratio	: -
Input signal	: -
System	: 2-way bass-reflex
Full range speaker	: -
Bass speaker	: 30 cm (12", BEYMA)
Midrange speaker	: -
Tweeter	: 25 mm (1")dyn. mid-high range speaker(44 mm voice coil, BEYMA)
Number of speakers	: 2
Speaker size	: 30 cm (12")
Sensitivity	: 97 dB/W/m
Max. rated SPL	: 124 dB
Radiation angle, horizontal	: -
Radiation angle, vertical	: -
Features	: -
Housing material	: birch plywood
Colour	: black
Mounting device	: -
Protected against ball rebound	: -
Protection class	: -
Admiss. ambient temp.	: 0-40 °C
Power supply	: -
Dimensions	: 350 x 612 x 382 mm
Width	: 350 mm
Height	: 612 mm
Depth	: 382 mm
Weight	: 18.92 kg



AV-Concept ApS
Glasmagervej 13, Fensmark
4684 Holmegaard
30 32 18 89
www.av-concept.dk

Inputs	: 1 x NEUTRIK SPEAKON
Outputs	: 1 x NEUTRIK SPEAKON par. out
Replacement voice coil	: -
Other features	: -
Accessories	: BAG-12M, MHB-12, MVB-12