

PA-806DAP - PA Mixing Amplifier



Mono class D PA mixing amplifier,
with integrated MP3 player, FM/DAB+ tuner and Bluetooth.

- 1 x 60 W
- Class D concept with high efficiency to cut energy costs
- Bluetooth version 4.2
- MP3 player with USB/SD interface, FM/DAB+ radio, LED display, infrared remote control
- Reception of interference-free 'digital radio' (DAB+)
- 1 balanced XLR microphone input with 48 V phantom power and priority selection for announcements
- 2 unbalanced inputs, switchable mic/line
- 2 unbalanced line inputs
- 1 TEL input
- 1 Music-On-Hold output (MOH)
- Speaker outputs via screw terminals
- Mute contact via screw terminals
- 2 line outputs
- Input level control and output level control
- 2-way tone control for the output



AV-Concept ApS
Professionelt AV-Udstyr

AV-Concept ApS
Glasmagervej 13, Fensmark
4684 Holmegaard
30 32 18 89
www.av-concept.dk

- Temperature-controlled fan
- LEDs for indicating operation, clipping, protect and signal level

Technical data:

Peak output power	: -
Power rating	: 60 W
Power rating at 2 Ohm	: -
Power rating at 4 Ohm	: -
Power rating at 8 Ohm	: -
Power rating at 16 Ohm	: -
Power rating at 100 V	: -
Power rating with 4 Ohm bridged operation	: -
Power rating with 8 Ohm bridged operation	: -
Output impedance	: -
Channels	: 1
Zones	: 1
Inputs	: 4.5 mV/600 Ω Ohm (channel 1), 4.5 mV/120 mV (channels 2-3), 60 mV (channels 4-5) 90 mV (tel.)
Attenuation factor	: -
Frequency range	: 60-15,000 Hz
Crossover network	: -
Crossover frequency	: -
Integrated limiter	: -
Equalizer bass	: yes
Equalizer midrange	: -
Equalizer treble	: yes
S/N ratio	: 72 \hat{A} dB (mic, channels 1-3) 85 \hat{A} dB (line, channels 2-5)
Crosstalk attenuation	: -
THD	: < 0.5%
Phantom power	: 48 V
Mains voltage	: \sim ; 230 V
Mains frequency	: 50 Hz
Power consumption, operation	: 160 VA
Power consumption, standby	: -
Standby current	: -
Operating voltage (possible alternative)	: DC 24 V

Power supply (possible
alternative)
Admiss. ambient temp.
Width
Height

MONACOR

: 4.2 A

: 0-40 °C

: 320 mm

: 95 mm

AV-Concept ApS
Professional AV-Udstyr



AV-Concept ApS
Glasmagervej 13, Fensmark
4684 Holmegaard
30 32 18 89
www.av-concept.dk

Depth	: 245 mm
Rack spaces, RS	: -
Weight	: 4.5 kg
Connections	: 1 x XLR (channel 1), 2 x 6.3 mm jack (channels 2-3), 2 x RCA L/R (channels 4-5), 2 x RCA (record out), 1 x F jack (FM/DAB+), screw terminals (tel. input, MOH, DC 24 V, speakers, mute)

Packing dimensions (W x H x L) : -

Gross weight	: 5.17 kg
Net weight	: 4.48 kg